



## **SPESCOAT WOOD-OIL and SPESCOAT WOOD-OIL PLUS**

**DESCRIPTION:** SPESCOAT WOOD-OIL is a hard wearing oil/resin penetrating timber finish for use on exterior and some interior timber surfaces. WOOD-OIL contains a fungicide and is therefore resistant to mould attack and is formulated to resist darkening with age. WOOD-OIL is non film forming so cannot crack peel or blister.

**USES:** WOOD-OIL is suitable for use on exterior cladding, windows, fascias, pergolas, decking and garden furniture. It may also be used on interior timber floors where an "oiled look" is preferred. In exterior situations where the timber is fully exposed to the sun, when correctly applied, WOOD-OIL should be re-coated approx. every 9-12 months.

**PLUS:** SPESCOAT WOOD-OIL is available as a true clear and as SPESCOAT WOOD-OIL PLUS. SPESCOAT WOOD OIL PLUS contains a small quantity of transparent iron oxide yellow pigment. It is not enough pigment to introduce any significant colour change on timber when compared to SPESCOAT WOOD-OIL. The addition of the transparent pigment significantly increases the life of the oil on timber.

**DIRECTIONS EXTERIOR:** New uncoated exterior timber should be flood brushed with one coat of SPESCOAT DEEPTREAT prior to applying WOOD-OIL. Particular attention should be paid to joints, nail holes and cut ends. WOOD-OIL is supplied ready for use, and should be applied unthinned. Apply by brush or roller as a two to three coat system. Should an excess of WOOD-OIL pool on the surface after the final coat, lightly wipe off any excess with a soft cloth before allowing to dry.

**DIRECTIONS INTERIOR:** New timber joinery or sanded floors may be coated as a saturate system, where the floor is flood coated with WOOD-OIL to allow maximum penetration. Any remaining excess WOOD-OIL pooling on the surface should be wiped off. The floor can then be machine dry buffed to achieve a matt polished effect.

**FLOOR MAINTENANCE:** As WOOD-OIL is non film forming it simply needs recoating as required. Each application continues to harden the surface. It is important to keep floor free of sand or grit. Regular sweeping and occasional mopping is all that is required. Placing dust collecting mats at entrance doors will help reduce surface wear.

**PREVIOUSLY VARNISHED OR PAINTED FLOORS:** Any paint or varnish must be completely removed prior to applying WOOD-OIL. Exterior decks that have been badly weathered or stained may be restored using SPESCOAT TIMBER-CLEAN before oiling.

**CLEAN UP:** Clean equipment with mineral turpentine. Do NOT clean hands with solvents, use a suitable hand cleaner.

**THINNING:** Not recommended.

**DRYING TIME:** 2 - 8 hours depending on temperature. Recoat is possible as soon as previous coat is dry. Interior surfaces will take longer to fully harden therefore on floors, light traffic is recommended for the first few days. Do not apply product at temperatures below 10°C or above 30°C or when relative humidity is greater than 80%. Do not apply in direct sun or to very hot or cold timber.

**COVERAGE:** Hardwoods 9-12 m<sup>2</sup>/Litre, Softwoods 7-10 m<sup>2</sup>/Litre, Rough sawn softwoods 6-8 m<sup>2</sup>/Litre.

Date Issued: 1/4/10

### **Shipway Spescoat**

A division of Topline Paint Pty Ltd

130 Halifax St. Adelaide S.A. 5000

Ph (08) 8223-1124 Fax (08) 8223-2045

Email: [info@shipways.com.au](mailto:info@shipways.com.au)

Web Site: [www.shipways.com.au](http://www.shipways.com.au)

**DISCLAIMER:** The above information is given in good faith as a general reference guide, no guarantee or warranty is expressed or implied. Any circumstances not covered by these instructions should be referred to SHIPWAY SPESCOAT or its agents for any particular attention required. All products are manufactured to exacting quality standards. There are however many factors that may affect the outcome of projects using our products that are beyond our control. SHIPWAY SPESCOAT cannot be responsible for poor climatic conditions, inadequate surface preparation, poor application techniques, failure to properly observe curing times, improper thinning or any variable beyond our control. Forminex® and Spescoat® are registered trademarks of Topline Paint Pty Ltd.



**COLOUR:** Light honey colour. Also available in a range of highly transparent tinted colours.

**PACKAGING:** Available in 1L, 4L, cans and 20L pails.

### **SAFETY INFORMATION SUMMARY:**

*The following information is a general guide only. Industrial users (ie where the product is being used in the workplace) are legally required to have available a Material Safety Data Sheet on this product. If you are unsure if you have an MSDS on this product please contact Shipway Spescoat and one will be provided. MSDS's are also readily available from our web site [www.shipways.com.au](http://www.shipways.com.au).*

**Safety Directions:** **KEEP OUT OF REACH OF CHILDREN – DO NOT SWALLOW.** Breathing the vapour is harmful and may cause lung irritation. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well ventilation conditions that prevent inhalation of vapours, dust or mist. Use the appropriate breathing equipment (refer to Aust Stand. 1716) when ventilation is restricted. Keep containers closed when not in use. Eliminate any source of ignition (open fires, pilot lights, furnaces, spark producing switches etc.) as this product is flammable. **DO NOT SMOKE.** Take precautionary measures against static discharges. Used clean up rags may spontaneously ignite. To avoid ignition immerse in water or store in a sealable glass container.

**First Aid Instructions:** If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor. If swallowed, **DO NOT INDUCE VOMITING** drink plenty of water and seek medical advice. Contact a Doctor of Poisons Information Centre (Phone 131126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation occurs seek prompt medical advice. Immerse contaminated clothing in water for 24 hours and do not use until laundered. In case of eye contact, hold eyes open and flood with running water for at least 15 minutes seek medical advice.

**Leaks, Spills and Disposal:** To prevent ignition of fumes product shut off all ignition sources. Contain or shut off leak if safe to do so. For large leaks or spills of volatile, flammable product, use respiratory protection, protective apparel and footwear. Spills should be absorbed either with rags (small spill) or dry sand/earth (large spill). In the case of flammable product spillage, use spark free implements to place rags or absorbed material into a solvent resistant container. Cover with water for 24 hours before disposal. DO NOT pour left over product down the drain – retain it in marked sealed container for future use or disposal through chemical waste collection programs. Dried empty cans can be recycled and should be disposed of via council steel recycling facilities.

**Fire:** Use foam and breathing apparatus. Avoid breathing products of combustion

---

Manufactured by : **SHIPWAY SPESCOAT**  
130 Halifax Street ADELAIDE S.A.5000 Phone (08) 8223 1124 Fax.(08) 8223 2045  
Visit our web site [www.shipways.com.au](http://www.shipways.com.au)

---

Date Issued: 1/4/10

### **Shipway Spescoat**

A division of Topline Paint Pty Ltd

130 Halifax St. Adelaide S.A. 5000

Ph (08) 8223-1124 Fax (08) 8223-2045

Email: [info@shipways.com.au](mailto:info@shipways.com.au)

Web Site: [www.shipways.com.au](http://www.shipways.com.au)

**DISCLAIMER:** The above information is given in good faith as a general reference guide, no guarantee or warranty is expressed or implied. Any circumstances not covered by these instructions should be referred to SHIPWAY SPESCOAT or its agents for any particular attention required. All products are manufactured to exacting quality standards. There are however many factors that may affect the outcome of projects using our products that are beyond our control. SHIPWAY SPESCOAT cannot be responsible for poor climatic conditions, inadequate surface preparation, poor application techniques, failure to properly observe curing times, improper thinning or any variable beyond our control. Forminex® and Spescoat® are registered trademarks of Topline Paint Pty Ltd.