


813 Premium Gloss Enamel

ISSUED: 28 April 2014

Page 1 of 2

**USE****THINNER/CLEAN**
Turpentine**APPLICATION****RE-COAT**
24 Hrs**HAZARD**

Durable, traditional long oil alkyd based enamel which displays a brilliant gloss and is hard wearing. Whilst 813 Premium Gloss Enamel is a relatively hard paint film it is still flexible enough to be suitable for interior and exterior use and is available in a wide range of colours based on pigments selected for their long term light-fastness and opacity.

USES: 813 Premium Gloss Enamel can be used as an interior or exterior finishing paint for all suitably primed and under-coated surfaces, wherever a high gloss finish is desired.

SURFACE PREPARATION:

New Timber Interior: Fill imperfections, sand smooth and apply 825 Superhide Undercoat.

New Timber Exterior: Fill imperfections, sand smooth and apply 809 Pink Wood Primer and 825 Superhide Undercoat.

Galvanised Iron: Prime with 66 Epoxy Undercoat.

Plaster, Asbestos, Brick, Masonry: Fill surface imperfections, sand smooth & dust down. Apply 1 coat of 824 Acrylic Undercoat.

Previously Painted Surfaces: Scrape off loose and flaking paint. Remove all glossy and powdery surfaces by sanding. Fill nail holes, cracks and imperfections, sand smooth and dust down. Sand gloss and semi gloss surfaces thoroughly and wipe clean. Spot prime any bare areas with the appropriate primer or sealer.

APPLICATION: Stir thoroughly until product is uniform. Apply by brush, roller or spray equipment. Allow 24 hours for any previous coats to dry thoroughly before applying 813 Premium Gloss Enamel.

THINNING: Ready for use by brush or roller application. Mineral Turps or Natural Turpentine can be added sparingly to aid brush or roller application properties. Mineral Turps or F-200 reducer may be used for spray application.

CLEAN UP: Mineral Turps.

DRYING: Touch dry 4-6 hours. Hard dry to handle 24 hours at 25°C. 813 Premium Gloss may be re-coated after overnight drying.

COLOUR: Full range of decorative and trim colours.

FINISH: High gloss.

COVERAGE: Theoretical coverage is 13-15 m² per Litre at 40 micron dry film thickness.

PACK SIZES: 1 litre, 4 litre

VEHICLE TYPE: Long oil alkyd.

PIGMENT TYPE: Titanium Dioxide, selected lead free colour pigments.

FILM PROPERTIES:

Solvent Resistance	Fair.	Chemical Resistance	Fair.
Abrasion Resistance	Good.	Impact Resistance	Good.
Heat Resistance	Good up to 100°C [pastel colours may yellow]	Flexibility	Good.

OTHER DETAILS: Highly recommended for high wear applications such as cupboard doors, doors or architraves. For an alternative product consider our 729 H2O Water Based Enamel either in a Gloss or Satin finish.

TOPLINE PAINT PTY LTD

Telephone: (08) 8384 1188

33 ALDERSHOT ROAD, LONSDALE, SOUTH AUSTRALIA 5160.

Fax: (08) 8326 1824

E-mail: admin@toplinepaint.com.au

Customers need to appreciate that as Topline Paint cannot control the conditions under which our products are used, we therefore are unable to guarantee suitability or accuracy in every situation. If any doubt exists, do check with our technical people. Before large-scale use always test on a small sample and ascertain suitability. No warranties express or implied are made. The risks and liability arising from handling, storage, use and compliance with legal restrictions, rests with the buyer.





813 Premium Gloss Enamel

PRECAUTIONS:

The following information is a general guide only. Industrial users (ie where the product is being used in the workplace) are legally required to have available a Material Safety Data Sheet on this product. If you are unsure if you have an MSDS on this product please contact Topline Paint and one will be provided.

Safety Directions: **KEEP OUT OF REACH OF CHILDREN – DO NOT SWALLOW.** Breathing the vapour is harmful and may cause lung irritation. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well ventilation conditions that prevent inhalation of vapours, dust or mist. Use the appropriate breathing equipment (refer to Aust Stand. 1716) when ventilation is restricted. Keep containers closed when not in use. Eliminate any source of ignition (open fires, pilot lights, furnaces, spark producing switches etc.) as this product is flammable. **DO NOT SMOKE.** Take precautionary measures against static discharges. Used clean up rags may spontaneously ignite. To avoid ignition immerse in water or store in a sealable glass container.

First Aid Instructions: If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor. If swallowed, **DO NOT INDUCE VOMITING** drink plenty of water and seek medical advice. Contact a Doctor of Poisons Information Centre (Phone 131126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation occurs seek prompt medical advice. Immerse contaminated clothing in water for 24 hours and do not use until laundered. In case of eye contact, hold eyes open and flood with running water for at least 15 minutes seek medical advice.

Leaks, Spills and Disposal: To prevent ignition of fumes product shut off all ignition sources. Contain or shut off leak if safe to do so. For large leaks or spills of volatile, flammable product, use respiratory protection, protective apparel and footwear. Spills should be absorbed either with rags (small spill) or dry sand/earth (large spill). In the case of flammable product spillage, use spark free implements to place rags or absorbed material into a solvent resistant container. Cover with water for 24 hours before disposal. DO NOT pour left over product down the drain – retain it in marked sealed container for future use or disposal through chemical waste collection programs. Dried empty cans can be recycled and should be disposed of via council steel recycling facilities.

Fire: Use foam and breathing apparatus. Avoid breathing products of combustion.

Hazard: The coloured square at the top of page 1 is provided for a quick reference as to the hazard level of a product. Blue refers to coatings with low hazard (eg water based wall paints). Yellow refers to medium hazard products such as QD enamels, which contain solvents, are flammable and need respirators for vapour protection. Red refers to products with special hazards such as isocyanate cured two pack finishes