

## 962 Hi Fix Primer



USE



THINNER/CLEAN

Water



APPLICATION



RE-COAT

2 - 3 Hrs

HAZARD



*A water based polymer acrylic primer and sealer designed for the complete and rapid sealing of porous surfaces such as concrete and Masonry.*

**USES:** Ideally suited for use as a sealer of paper-faced wallboards and other porous surfaces such as unglazed brick, masonry, Hardiplank sheeting, concrete and cement.

**SURFACE PREPARATION:** Ensure all surfaces are clean, relatively dry and free from oil, wax and grease and dust. Any loose or drummy material should be removed and the area patched or repaired.

**APPLICATION:** Stir thoroughly until product is uniform. 962 Hi Fix Primer is designed for brush, roller or airless spray application. Do not use whilst temperatures are below 10°C or where the relative humidity is greater than 85% as it may cause defects in the film formation.

**THINNING:** For normal applications, mix one part of Hi-Fix Primer with three parts water by volume. Stir well before use. In more difficult areas such as cool-rooms, wet areas and such like use a mix ratio of one part Hi-Fix to 1.5 parts water.

**CLEAN UP:** Wash out brushes and equipment in water.

**DRYING:** Surface dry in 30 minutes. Re-coating is possible after 2 hours at 25°C.

**COLOUR:** Clear.

**FINISH:** Gloss

**COVERAGE:** Theoretical coverage is 10 m<sup>2</sup>/Litres of mixed (thinned) material.

**PACK SIZES:** 1 litre, 4 Litre, 20 Litre.

**VEHICLE TYPE:** Modified acrylic emulsion.

### FILM PROPERTIES:

|                     |       |                     |       |
|---------------------|-------|---------------------|-------|
| Solvent Resistance  | Fair. | Chemical Resistance | Fair. |
| Abrasion Resistance | Fair. | Impact Resistance   | Good. |
| Heat Resistance     | Fair. | Flexibility         | Good. |

**TOPLINE PAINT PTY LTD**

Telephone: (08) 8384 1188

**33 ALDERSHOT ROAD, LONSDALE, SOUTH AUSTRALIA 5160.**

Fax: (08) 8326 1824

E-mail: [admin@toplinepaint.com.au](mailto:admin@toplinepaint.com.au)

Customers need to appreciate that as Topline Paint cannot control the conditions under which our products are used, we therefore are unable to guarantee suitability or accuracy in every situation. If any doubt exists, do check with our technical people. Before large-scale use always test on a small sample and ascertain suitability. No warranties express or implied are made. The risks and liability arising from handling, storage, use and compliance with legal restrictions, rests with the buyer.





## 962 Hi Fix Primer

### PRECAUTIONS:

*The following information is a general guide only. Industrial users (ie where the product is being used in the workplace) are legally required to have available a Material Safety Data Sheet on this product. If you are unsure if you have an MSDS on this product please contact Topline Paint and one will be provided.*

**Safety Directions:** **KEEP OUT OF REACH OF CHILDREN – DO NOT SWALLOW.** Breathing the vapour is harmful and may cause lung irritation. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well ventilation conditions that prevent inhalation of vapours, dust or mist. Use the appropriate breathing equipment (refer to Aust Stand. 1716) when ventilation is restricted. Keep containers closed when not in use. Eliminate any source of ignition (open fires, pilot lights, furnaces, spark producing switches etc.) as this product is flammable. **DO NOT SMOKE.** Take precautionary measures against static discharges. Used clean up rags may spontaneously ignite. To avoid ignition immerse in water or store in a sealable glass container.

**First Aid Instructions:** If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor. If swallowed, **DO NOT INDUCE VOMITING** drink plenty of water and seek medical advice. Contact a Doctor of Poisons Information Centre (Phone 131126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation occurs seek prompt medical advice. Immerse contaminated clothing in water for 24 hours and do not use until laundered. In case of eye contact, hold eyes open and flood with running water for at least 15 minutes seek medical advice.

**Leaks, Spills and Disposal:** To prevent ignition of fumes product shut off all ignition sources. Contain or shut off leak if safe to do so. For large leaks or spills of volatile, flammable product, use respiratory protection, protective apparel and footwear. Spills should be absorbed either with rags (small spill) or dry sand/earth (large spill). In the case of flammable product spillage, use spark free implements to place rags or absorbed material into a solvent resistant container. Cover with water for 24 hours before disposal. DO NOT pour left over product down the drain – retain it in marked sealed container for future use or disposal through chemical waste collection programs. Dried empty cans can be recycled and should be disposed of via council steel recycling facilities.

**Fire:** Use foam and breathing apparatus. Avoid breathing products of combustion.

**Hazard:** The coloured square at the top of page 1 is provided for a quick reference as to the hazard level of a product. Blue refers to coatings with low hazard (eg water based wall paints). Yellow refers to medium hazard products such as QD enamels, which contain solvents, are flammable and need respirators for vapour protection. Red refers to products with special hazards such as isocyanate cured two pack finishes